



Scully Rack Tester

The most advanced, ATEX Approved rack control tester



The **NEW Scully Rack Tester** is an advanced, comprehensive, portable tester approved for testing in hazardous locations. It allows Scully customers and field personnel to quickly assess any Scully overflow prevention, grounding and vehicle identification rack controller for proper equipment operation. In the event of a malfunction, it facilitates problem isolation and resolution.

THE SCULLY UNIVERSAL RACK TESTER SIMULATES:

- Optic and Thermistor Overflow Sensors
- Scully Ground Bolts & Ground Balls
- Scully T.I.M.™ Truck Identification Modules

ORDERING INFORMATION

Description	Part Number
Scully Rack Tester	09832

TECHNICAL SPECIFICATION

Power Supply: Powered by loading rack control unit under test.

Dimensions: 27.4 cm long x 24.8 cm wide x 12.1 cm high

Weight: 2.86 kg

Connection: The rack controller plug connects to one of three style sockets on the front of the tester.

APPROVALS

The Scully Rack Tester has safety approvals as an intrinsically safe testing device.

Ex ia IIB T4 Ga



Entity Parameters

$U_i = 15V$, $I_i = 250mA$, $P_i = 1.0W$, $C_i = 1.25\mu F$, $L_i = 0$

$U_m = 15Vdc$

Pollution Degree 2

Ambient temperature for all ratings

($T_a \leq 0^\circ C$ to $\leq 60^\circ C$) at 95% humidity

Maximum Altitude = 6562 ft. (2000 m)



Meridian House, Unit 33, 37 Road One Winsford Industrial Estate, Winsford Cheshire CW7 3QG, UK
+44 (0) 1606 553805 • sales@scullyuk.com

Patent Pending
Copyright © 2016 Scully Signal Company. Dynacheck, Dynamic Self-Checking, Dynamic Self-Testing, Faylsafe, IntelliCheck, Intellitrol are registered trademarks of Scully Signal Company.
All Rights Reserved. Specifications are subject to change without notice.
Scully Rack Tester_Rev A_UK- March 2016