

Setting Standards in Safety and Dependability since 1936.

The Most Popular Delivery Nozzles in the World with Increased Hose Flexibility and Freedom of Movement

- The leading choice for light product, high volume deliveries.
- Reduced pressure drop allows for faster pumping speeds.
- Prevent closing shock to prolong truck equipment life.
- Feature leak-proof filling and no-drip operation.
- Original ball valve design and deadbolt locking handle.
- Advanced ball bearing design allows for easy rotation at all operating pressures.
- Teflon high recovery seal and shielded bearings for optimum field performance.
- No nipple required to attach hose with male style swivels.
- Lightweight aluminum and zinc construction.
- Wide variety of liquid product use.

Materials

- Aluminum body.
- Hard chrome plated brass ball valve.
- Teflon ball seat.
- Delrin ball follower.
- Aluminum and zinc swivel body.
- Teflon swivel seal.
- Viton seals.

Options

- 5 P.S.I. anti-drip valve.
- Without swivel.
- Sightglass.
- Special chemicals.

 Consult Scully for part numbers.

Flow Rates

 Used for deliveries up to 450 L.P.M

ORDERING INFORMATION	
Description	Part Number
LS, 1.5 X 1.5 BSP/3 PSI	05028
SS, 1.5 BSP X UNI/3PSI	05076
SS, 1.5 X 1.5 BSP/5 PSI, Non-anodized	05111
SS, 1.5 X 1.5 BSP/3 PSI	05125
SS, 1.5 X 1.5 BSP/5 PSI	05124

Description	Part Numbe
Nozzle Rebuild Kit	05416
Seal kit, no swivel parts	05415
	No.

05416 Nozzle Rebuild Kit

REPLACEMENT KITS

05415 Nozzle Seal Kit

Copyright © 2016 Scully Signal Company. Dynacheck, Dynamic Self-Checking, Dynamic Self-Testing, Faylsafe, Golden Gallon, IntelliCheck, Intellitrol, Mark IV, Sculclamp, Sculflow, Sculmatic, Twis-Lok, Unifil, Ventafil, Ventalarm, V.I.P. and Whistler are registered trademarksof Scully Signal Company. All Rights Reserved. Specifications are subject to change without notice.

Rev A January 2016

